

KR840RLS

Roller Registration

Convert 1 to 4 up incoming products to a single stream and accurately register a wide range of large products. Designed to change product flow ninety degrees either right or left of the incoming product flow. Integrated controls allow for easy speed matching, stopping and starting with a Kirk-Rudy base.

*Accurately
bump-turn
and register
large products*

- Handles product up to 17" long
- Converts 1 - 4 up into single stream
- Hand crank moveable table
- Air assist for faster speeds
- Adjustable outfeed speed-up

- ✓ *Heavy duty*
- ✓ *Easy set-up*



KR840RLS

Roller Registration

Convert 1-4 up products into a single stream.

FEATURES:

- Dual height adjustable skid bar
- Micro adjustment registration
- Adjustable pinch rollers
- Hand crank moveable table
- Air assist for higher speeds
- Adjustable outfeed speed-up

OPTIONS:

- Stand-alone controls
- Round or flat belt cross feed conveyoyr
- Hydralift (5" and 7")
- Right to left, left to right, and/or straight thru registration



** General Specifications

Product Capacity

Width	Min 3" (7.6 cm)	Max 25" (63.5 cm)
Length	Min 3" (7.6 cm)	Max 17" (43.18 cm)
Thickness	Min .004" (.18 mm)	Max .25" (6.35 mm)

Operating Speeds

Maximum	Variable to 400 feet per minute
---------	---------------------------------

Note: Speeds are dependent on material being fed

Physical

	English	Metric
Length	64.5"	163.8 cm
Width	52.5"	133.4 cm
Height	39"	99 cm
Weight	800 lbs.	362.87 kg.

Electrical Requirements

Voltage	Amp	Phase	Hz
220 VAC	20	1	50/60

Compressed Air: 80 psi @ 4scfm



**Specifications subject to change without notice.

Ph: 770.427.4203

www.kirkrudy.com